



JLM VI

Für Gerad- und Schrägschliff
 For straight and alternate bevel grinding
 Pour l'affûtage droit et à biseau
 Per affilatura diritta ed obliqua
 Para el afilado recto y en bisel

Kreissägen	Circular saws	Scies circulaires	Seghe circolari	Sierras circulares	50 - 600 mm \varnothing
Bandsägen	Bandsaws	Scies à ruban	Seghe a nastro	Sierras de cinta	5 - 60 mm
Zahnweite	Tooth pitch	Pas de denture	Passo denti	Paso de dientes	Max. 40 mm
Zahnhöhe	Tooth depth	Hauteur des dents	Altezza denti	Altura de dientes	Max. 20 mm
Schrägschliff	Face bevel	Affûtage à biseau	Affilatura obliqua	Afilado en bisel	10° und / and / et 20°
Spanwinkel	Cutting angle	Angle de coupe	Angolo di taglio	Angulo de corte	0 - 30°
Vorschubge- schwindigkeit	Rate of grinding	Vitesse d'avantement	Velocità di avanzamento	Velocidad de afilado	30, 45, 60 und / and / et 90
Schleifscheibe	Grinding wheel	Meule	Mola	Muela	150 x 25 mm
Kraftbedarf	Power input	Puissance	Potenza motori	Potencia de los motores	0,8 PS, H.P., CV.
Nettogewicht	Net weight	Poids net	Peso netto	Peso neto	195 kg