



JLM 36/2

Für Gerad- und Schrägschliff
 For straight and alternate bevel grinding
 Pour l'affûtage droit et à biseau
 Per affilatura diritta ed obliqua
 Para el afilado recto y en bisel

Kreissägen	Circular saws	Scies circulaires	Seghe circolari	Sierras circulares	200-1500 mm ϕ
Bandsägen	Bandsaws	Scies á ruban	Seghe a nastro	Sierras de cinta	10 - 250 mm
Gattersägen	Frame (Gang) saws	Scies alternatives	Seghe alternative	Sierras alternativas	Alle Größen, all sizes, toutes dimensions
Zahnweite	Tooth pitch	Pas de denture	Passo denti	Paso de dientes	max. 70 mm
Zahnhöhe	Tooth depth	Hauteur des dents	Altezza denti	Altura de dientes	max. 45 mm
Schrägschliff	Face bevel	Affûtage α biseau	Affilatura obliqua	Afilado en bisel	0 - 20°
Spanwinkel	Cutting angle	Angle de coupe	Angolo di taglio	Angulo de corte	0 - 25°
Vorschubgeschwindigkeit	Rate of grinding	Vitesse d'avancement	Velocità di avanzamento	Velocidad de afilado	35 und/and/et 70
Schleifscheibe	Grinding wheel	Meule	Mola	Muela	250 x 25 mm
Kraftbedarf	Power input	Puissance	Potenza motori	Potencia de los motores	1 PS, H.P., CV.
Nettogewicht	Net weight	Poids net	Peso netto	Peso neto	385 kg.